

Amendments To The Claims

The following listing of claims replaces all prior listings of claims:

Listing of Claims:

1. (Currently Amended) A repeater that mediates traffic between a network transceiver and a user transceiver in a wireless communication system comprising:
 - a network unit that maintains a network link with the network transceiver;
 - a user unit that maintains a user link with the user transceiver;
 - a two-way communication pathway between the network unit and the user unit adapted to facilitate signal communication between the network transceiver and the user transceiver in autonomous repeater hops between the network transceiver and the network unit, between the user transceiver and the user unit, and between the network unit and the user unit; and
 - ~~a beam-formers~~ beam-former unit respectively coupled to each of the network unit and the user unit, ~~and each beam-former unit being~~ adapted to communicate signals in an operating frequency band of the network transceiver ~~and or user transceivers transceiver~~, and to control effective radiated power to maximize radio frequency isolation between the network unit and the user unit;
 - the signal communication between the network unit and the user unit having a signal waveform that is independent of the operating frequency band of the signal communication between the network and user transceivers.
2. (Original) The repeater according to Claim 1 wherein:
 - the beam-formers are adapted to control effective radiated power to increase coverage area of the riser unit.
3. (Original) The repeater according to Claim 1 wherein:
 - the beam-formers are adapted to control effective radiated power to improve link quality of the network unit.

4. (Original) The repeater according to Claim 1 further comprising:
transmit antennas coupled to the beam-formers whereby the transmit antennas
operate at the network and user transceiver operating frequency and the beam-formers control
effective radiated power of the network unit and user unit to increase coverage area of the user unit.

5. (Original) The repeater according to Claim 1 further comprising:
receiver antennas respectively coupled to the beam-formers whereby the receiver
antennas operate at the network and user transceiver operating frequency and the beam-formers
control antenna radiation patterns of the network unit and user unit to increase coverage area of the
user unit.

6. (Original) The repeater according to Claim 1 wherein:
the autonomous repeater hop between the network unit and the user unit is tuned to
operate at a frequency band selected from a group consisting of an Unlicensed National Information
Infrastructure (U-ISM) spectrum frequency band, an Unlicensed Personal Communication Services
(U-PCS) spectrum frequency band, an Industrial, Scientific and Medical (ISM) spectrum frequency
band, and any unlicensed frequency band.

7. (Original) The repeater according to Claim 1 further comprising:
a gain controller that compensates for propagation losses between the network unit
and user unit alone.

8. (Original) The repeater according to Claim 1 further comprising:
a gain controller that compensates at least for propagation losses between the
network unit and user unit alone.

9. (Original) The repeater according to Claim 1 further comprising:
the network unit configured to be placed exterior to a structure;
the user unit configured to be placed interior to the structure; and
a gain controller that compensates for indoor-outdoor propagation losses alone.

10. (Original) The repeater according to Claim 1 wherein:
the autonomous repeater hop between the network unit and the user unit on the communication pathway communicates on a carrier signal that is independent of signals communicated between the repeater and the network and user transceivers.
11. (Original) The repeater according to Claim 1 wherein:
the autonomous repeater hop between the network unit and the user unit on the communication pathway communicates at a carrier frequency that is independent of signals communicated between the repeater and the network and user transceivers.
12. (Original) The repeater according to Claim 1 wherein:
the autonomous repeater hop between the network unit and the user unit on the communication pathway communicates with a signal waveform that is independent of signal waveform communicated between the repeater and the network and user transceivers.
13. (Original) The repeater according to Claim 1 further comprising:
dedicated wireless data and/or control links in the communication pathway between the network unit and the user unit operating at unlicensed frequency bands.
14. (Original) The repeater according to Claim 1 further comprising:
dedicated wireless proprietary data and/or control links in the communication pathway between the network unit and the user unit operating at unlicensed frequency bands.
15. (Original) The repeater according to Claim 1 further comprising:
dedicated wireless data and/or control links in the communication pathway between the network unit and the user unit based on a wireless standard.
16. (Original) The repeater according to Claim 1 further comprising:
dedicated wireless data and/or control links in the communication pathway between the network unit and the user unit that are power-controlled for operation at reduced transmit power.

17. (Original) The repeater according to Claim 1 further comprising:
dedicated wire-line data and/or control links in the communication pathway between
the network unit and the user unit selected from among links in a group consisting of electric wires,
telephone lines, and coaxial cables.

18. (Original) The repeater according to Claim 1 further comprising:
dedicated wire-line data and/or control links in the communication pathway between
the network unit and the user unit based on a wireline standard.

19. (Original) The repeater according to Claim 1 further comprising:
an in-band or out-of-band control link in the communication pathway between the
network unit and the user unit.

20. (Original) The repeater according to Claim 1 further comprising:
a wireless control link in the communication pathway between the network unit and
the user unit selected from among a group consisting of Bluetooth, any 802.11-based standard, and
other wireless standards.

21. (Original) The repeater according to Claim 1 further comprising:
a dedicated wireless or Wire-line proprietary control link in the communication
pathway between the network unit and the user unit based on frequency tones.

22. (Original) The repeater according to Claim 1 wherein the network unit
and/or the user unit further comprises:
a pair of antennas; and
a switch connected to the antenna pair that performs switching operations for
transmit/receive operations enabling switched antenna diversity in all or some repeater hops and
communication links.

23. (Original) The repeater according to Claim 1 further comprising:
local oscillators in the network unit and the user unit; and
a control and/or data link in the communication pathway from the network unit to
the user unit that carries a synchronization signal to mutually synchronize the local oscillators.

24. (Original) The repeater according to Claim 1 further comprising:
local oscillators in the network unit and the user unit that are synchronized using
mains electricity signal oscillations to mutually synchronize the local oscillators.
25. (Original) The repeater according to Claim 1 wherein:
the network unit and the user unit are assigned unique identification numbers.
26. (Original) The repeater according to Claim 1 further comprising:
an identification and reference frequency unit that generates a Binary Phase Shift
Keying (BPSK) signal modulated by the identification number, modulates the signal at a suitable part
of the operating unlicensed spectrum band, and couples the signal into a transmitter pathway of a
forward-link of the network unit.
27. (Original) The repeater according to Claim 1 further comprising:
an identification and location unit that modulates identification and location
information on a reverse link communication waveform n by coded low bit-rate modulation, the
modulation being amplitude modulation or Differential Quadrature Phase Shift Keying (DQPSK)
modulation.
28. (Currently Amended) ~~The repeater according to Claim 1 further comprising:~~
A repeater that mediates traffic between a network transceiver and a user transceiver in a wireless
communication system comprising:
a network unit that maintains a network link with the network transceiver;
a user unit that maintains a user link with the user transceiver;
a two-way communication pathway between the network unit and the user unit
adapted to facilitate signal communication between the network transceiver and the user transceiver
in autonomous repeater hops between the network transceiver and the network unit, between the
user transceiver and the user unit, and between the network unit and the user unit;
beam-formers respectively coupled to the network unit and the user unit and adapted
to communicate signals in an operating frequency band of the network and user transceivers and to
control effective radiated power; and

a calibration signal generator/transmitter that generates a spread-spectrum signal for complex channel impulse response generation.

29. (Currently Amended) ~~The repeater according to Claim 1 further comprising:~~
A repeater that mediates traffic between a network transceiver and a user transceiver in a wireless communication system comprising:

a network unit that maintains a network link with the network transceiver;

a user unit that maintains a user link with the user transceiver;

a two-way communication pathway between the network unit and the user unit adapted to facilitate signal communication between the network transceiver and the user transceiver in autonomous repeater hops between the network transceiver and the network unit, between the user transceiver and the user unit, and between the network unit and the user unit;

beam-formers respectively coupled to the network unit and the user unit and adapted to communicate signals in an operating frequency band of the network and user transceivers and to control effective radiated power; and

a calibration signal generator/transmitter that generates a spread-spectrum signal for complex channel impulse response generation using a code generation technique selected from one or more techniques from among a group consisting of:

generating spread-spectrum waveforms by Pseudo Random, Gold, or other code known *a priori* to all units;

generating code phase of a known code to uniquely-identify all user units and all network units;

allocating codes or code phases by dynamic assignment strategies;

using more than one code for complex channel impulse response generation; using more than one code phase for complex channel impulse response generation;

modulating the spread-spectrum signal by unit identifier; and

generating the spread-spectrum wave frequency in the operating cellular band or in an unlicensed band.

30. (Original) The repeater according to Claim 29 wherein:
the calibration signal generator/transmitter that generates the complex channel
impulse response using correlation.

31. (Original) The repeater according to Claim 29 wherein:
the calibration signal generator/transmitter that generates the complex channel
impulse response using matrix inversion.

32. (Currently Amended) ~~The repeater according to Claim 1 further comprising:~~
A repeater that mediates traffic between a network transceiver and a user transceiver in a wireless
communication system comprising:
a network unit that maintains a network link with the network transceiver;
a user unit that maintains a user link with the user transceiver;
a two-way communication pathway between the network unit and the user unit
adapted to facilitate signal communication between the network transceiver and the user transceiver
in autonomous repeater hops between the network transceiver and the network unit, between the
user transceiver and the user unit, and between the network unit and the user unit;
beam-formers respectively coupled to the network unit and the user unit and adapted
to communicate signals in an operating frequency band of the network and user transceivers and to
control effective radiated power; and
a calibration signal generator/transmitter that generates a complex channel impulse
response using correlation.

33. (Currently Amended) ~~The repeater according to Claim 1 further comprising:~~
A repeater that mediates traffic between a network transceiver and a user transceiver in a wireless
communication system comprising:
a network unit that maintains a network link with the network transceiver;
a user unit that maintains a user link with the user transceiver;
a two-way communication pathway between the network unit and the user unit
adapted to facilitate signal communication between the network transceiver and the user transceiver

in autonomous repeater hops between the network transceiver and the network unit, between the user transceiver and the user unit, and between the network unit and the user unit;

beam-formers respectively coupled to the network unit and the user unit and adapted to communicate signals in an operating frequency band of the network and user transceivers and to control effective radiated power; and

a calibration signal generator/transmitter that generates a complex channel impulse response using matrix inversion.

34. (Original) The repeater according to Claim 1 further comprising:
at least one amplifier that boosts a desired signal entering the repeater in part or all of an allocated signal spectrum.

35. (Original) The repeater according to Claim 1 further comprising:
the communication pathway between the network unit and the user unit has an operating band that is determined using a technique selected from one or more of a group consisting of preselecting the operating band, manually selecting the operating band, and automatically selecting the operating band based on detected signals.

36. (Original) The repeater according to Claim 1 further comprising:
at least one amplifier that boosts a desired signal entering the repeater whereby the signal is from wireless systems selected from one or more of a group consisting of Global System for Mobile Communications (GSM) and all its derivative systems, cdma2000 (Code Division Multiple Access), Wideband Code Division Multiple Access (WCDMA), and any other standards, and systems operating in cellular or wireless bands, as well as Global Positioning System (GPS).

37. (Original) The repeater according to Claim 1 further comprising:
directional antennas capable of mutual isolation of the network unit and the user unit operating in the boosted signal frequency band.

38. (Currently Amended) ~~The repeater according to Claim 1 further comprising:~~
A repeater that mediates traffic between a network transceiver and a user transceiver in a wireless communication system comprising:

a network unit that maintains a network link with the network transceiver;
a user unit that maintains a user link with the user transceiver;
a two-way communication pathway between the network unit and the user unit
adapted to facilitate signal communication between the network transceiver and the user transceiver
in autonomous repeater hops between the network transceiver and the network unit, between the
user transceiver and the user unit, and between the network unit and the user unit;

beam-formers respectively coupled to the network unit and the user unit and adapted
to communicate signals in an operating frequency band of the network and user transceivers and to
control effective radiated power; and

an echo canceller in each of the network and the user units, which mutually isolates
the network unit and the user unit and operates in a frequency band of a boosted signal.

39. (Currently Amended) ~~The repeater according to Claim 1 further comprising:~~
A repeater that mediates traffic between a network transceiver and a user transceiver in a wireless
communication system comprising:

a network unit that maintains a network link with the network transceiver;
a user unit that maintains a user link with the user transceiver;
a two-way communication pathway between the network unit and the user unit
adapted to facilitate signal communication between the network transceiver and the user transceiver
in autonomous repeater hops between the network transceiver and the network unit, between the
user transceiver and the user unit, and between the network unit and the user unit;

beam-formers respectively coupled to the network unit and the user unit and adapted
to communicate signals in an operating frequency band of the network and user transceivers and to
control effective radiated power; and

an echo canceller in each of the network and the user units, which inserts a delay in
boosted signals path.

40. (Currently Amended) ~~The repeater according to Claim 1 further comprising:~~
A repeater that mediates traffic between a network transceiver and a user transceiver in a wireless
communication system comprising:

a network unit that maintains a network link with the network transceiver;

a user unit that maintains a user link with the user transceiver;

a two-way communication pathway between the network unit and the user unit adapted to facilitate signal communication between the network transceiver and the user transceiver in autonomous repeater hops between the network transceiver and the network unit, between the user transceiver and the user unit, and between the network unit and the user unit;

beam-formers respectively coupled to the network unit and the user unit and adapted to communicate signals in an operating frequency band of the network and user transceivers and to control effective radiated power; and

an echo canceller in each of the network and the user units, that insert a delay in signal path, the delay being selected from a group consisting of a deliberate delay in the network unit, a deliberate delay in the user unit, and a deliberate delay in both the network unit and the user unit.

41. (Currently Amended) ~~The repeater according to Claim 1 further comprising:~~
A repeater that mediates traffic between a network transceiver and a user transceiver in a wireless communication system comprising:

a network unit that maintains a network link with the network transceiver;

a user unit that maintains a user link with the user transceiver;

a two-way communication pathway between the network unit and the user unit adapted to facilitate signal communication between the network transceiver and the user transceiver in autonomous repeater hops between the network transceiver and the network unit, between the user transceiver and the user unit, and between the network unit and the user unit;

beam-formers respectively coupled to the network unit and the user unit and adapted to communicate signals in an operating frequency band of the network and user transceivers and to control effective radiated power; and

a reverse-link pathway in the communication pathway between the network unit and the user unit, and the reverse-link between the network unit and the network transceiver are gated based on signal presence to reduce interference and power consumption.

42. (Original) The repeater according to Claim 1 wherein: the network unit is configured to operate with a plurality of user units.

43. (Currently Amended) The repeater according to Claim 1 wherein:
the network unit and user unit are mechanically attached ~~and configured~~
~~mechanically back-to-back in~~ within a single housing.

44. (Currently Amended) The repeater according to Claim 1 wherein:
the repeater operates in an unlicensed frequency band and is capable of selecting ~~an~~
the operating frequency band at a frequency that does not interfere with other devices operating in
the unlicensed frequency band.